

Quad Multi-Viewer Switch

Model:CQ7100

Features

- Support 1 X VGA, 2 X DP, 4 X HDMI (3 X compatible MHL) signal input.
- Support 1 X HDMI output, resolution up to 1920*1080 @60HZ.
- Input signals are all included audio, support audio and video synchronization switching, four-division mode audio independent switching.
- Built-in multiple presentation mode: 4 split screen / 2 split screen / PIP, POP / full screen.
- Control method: Panel button / Remote control / RS-232.

Diagram

Diagram

Supports 3 kinds of signals: HDMIx4ports + DPx 2ports + VGA+3.5mmx1ports,
Total 7 ports signal input



Specification

MODLE NAME	CQ7100
Input	4 x HDMI, 2 x DP, 1 x VGA 1 x 3.5mm
Output	1 x HDMI, 1 x 3.5mm
Video Resolution	1080P @60Hz
Code Depth	24bit, 1677 ten thousand
POP, PIP mode	Fixed model
Control mode	Panel button / Remote control / RS-232
Material	Metal
Power Supply	AC 110V-240V 50/60HZ DC 12V
Dimension (L x W x H)	278 x 166 x 36 mm
Mass (Main unit)	1.2Kg

Package connects

- 1 x 12V Power Supply
- 1 x IR (Without battery)
- 1 x User Manual