## Acafa Information Made in Taiwan



### Description



# **HDMI Matrix Switch**

MODEL: HDM4400

4X4 HDMI Matrix Switch Extender over CAT.5e/6

Diagram

Supports 4 different HDMI input source

HDMI #

VGA

VGA LCD

3

from TV, PC, Player, Camera,...etc. HDMI sources selectable by

push button or remote controler.

Made in Taiwan

It's the powerful solution for 4 x 4 HDMI Matrix Switch Extender over CAT.5e/6. Each receiver is capable of connecting another 2 receivers for further 100m (point-to-pint). The HDMI sources are selectable by front buttons or IR remote control

Easy and convenient to control the long-distance RS-232 devices over CAT.5e/6 and real-time monitor each content of 4 HDMI sources at local site. Features Diagram

- Supports 4 HDMI sources and the same or different contents can be shown on remote 4 HDMI displays at the same time.
- Supports HDMI 1.3, HDCP compliant.
- Supports resolution up to Full HD 1080p, 1920 x 1080 @60Hz.
- Each receiver (remote) links cascade-chainable 2 receivers.
- Extended distance over CAT. 5e/6up to 100m (point-to-point).
- HDMI sources selectable by front buttons or IR remote control.
- IR (Infrared Remote) enabled.
- Supports RS-232 (serial).
- Supports Local HDMI monitoring and Audio enabled.
- Made in Taiwan.

#### Accessories:

- 4 x IR Cable
- 4 x RS-232 Cable
- 1 X Rack Mount Brackets

PANIO

- 1 X DC 12V / 5A Power Adaptor
- 1 X Remote Control
- 1 X Audio Cable





Skype1:epanio Skype2:epanio1



Cat5e/6 100m

HDMI

HDMI LCD

HDMI

HDMI LCD

TTTT

VGA

VGA LCD



Local output

## Acafa Information Made in Taiwan



Model		HDM4400-Transmitter
ConsoleConnectors	HDMI Output	1x HDMI (Female)
	RS-232 Control Port	4 x3.5Ø jack
HDMI source	HDMI Input	4 x HDMI (Female)
Extension Port	RJ-45	Full HD 1080p AV Extension
RJ-45		4 (Line Out)
Audio		Supports Stereo Audio
IR		Unidirectional
	Power	Red LED
LED Indicators	Link	Green LED
	Selected HDMI source	Green LED for selected AV source
HDMI Source Select Button		5
DDC Supported		DDC2B
Extension Cable Type & Length		CAT.5e / CAT.6 Max. Length: 100m(point-to-point)
Max. Video Resolution Supported		Full HD 1080p,1920 x 1080 @60Hz
Housing material		Metal
Operating Temperature		32 - 122°F (0 - 50°C)
Power Supply		External DC 12V /5A Power Adaptor
Dimension (L x W x H )		440 x205 x42 mm
Humidity		0% - 80% RH







