

4K HDMI/ DP signal input 4-screen video wall splicer

Model:HW2250K

Features

- Built-in 1x2 1x3 1x4 2x2 2x1 3x1 4x1 video wall.
- Support 1 channel HDMI/ 1 channel DP interface switching input.
- Support the highest input resolution up to 3840X2160 60Hz/ 7680X1080.
- Support single display screen 90° 180° 270° rotation function.
- Support manual edge adjustment of images to solve the problem of screen movement caused by the display terminal during the splicing process.
- Support 3.5mm port audio separation output.
- Pure hardware design, plug and play, no need to install additional software.
- Image point-to-point lossless, portional,non-distorted, non-stretching display.
- Control method: remote control switching, panel ttons.

Specification

Model Name	HW2250K
Input	1 x HDMI, 1 x DP
Output	4 x HDMI, 1 x 3.5mm
Input resolution	1920x1080, 1920x2160, 1920x3240, 1920x4320, 3840x1080, 3840x2160 60Hz, 5760x1080, 7680x1080
Output resolution	Up to 1920x1080 60hz, 720p, 1920x1200
Splicing TV wall	1x2 1x3 1x4 2x2 2x1 3x1 4x1
Protocol standard	Support HDMI2.0, HDCP
HDMI cable length	Input and output can be connected to HDMI 4K cable up to 5 meters.
Control method	Remote control, panel button
Power	DC 12V/ 1.5A
Dimensions	223 x 104 x 27mm (LxWxH)

Diagram

Diagram



Package contents

- 1 X HW2250K
- 1 X 12V 1.5A Adapter
- 1 X Remote control (Battery not provided)
- 1 X User manual